



Care Instructions

Facade

Sealing RFS

RFS sealant can be applied to glazed Salamander outdoor. Because of sealing surface is closed and dirt particles only adhere superficially. Sealing causes the color to become more intensive in the course of time. The sealing RFS may explicitly only applied to previously glazed profile surfaces!

CLEANING: Dirt can be removed easily with a gentle jet of water (i.e. garden hose) and with a soft brush.

CARE/MAINTENANCE: Special care is not necessary (except for cleaning). Therefore, sanding and painting of the facade is not required in the long run. Finishing of the sealing in case of external mechanical damages is possible and recommended for aesthetic reasons only.

Glazing FVG

The surface is colorized by means of the transparent-colored glazes. Due to the open structure, dirt adheres to the surface more easily in comparison to a sealed surface. The color may become lighter in the course of time.

CLEANING: Dirt can easily be removed by means of a gentle jet of water (i.e. garden hose) and with a soft brush.

CARE/MAINTENANCE: If desired, the glaze can be freshened up in diluted form (e.g. 3:1 ratio with 3 parts of water – 1 part of glaze). Before the surface has to be carefully cleaned!

Salamander outdoor profiles, untreated

Due to the open structure, dirt deposits more easily in comparison to a sealed surface. Salamander outdoor profiles do not grey like wood. In the course of time, the color of a non-glazed facade can become lighter.

CLEANING: Dirt can easily be removed by means of a gentle jet of water (i.e. garden hose, high-pressure-cleaner with appropriate distance) and with a soft brush. Tenacious dirt (e.g. organic residues, fat) may also be removed by gentle sanding.

CARE/MAINTENANCE: Maintenance – except for regular cleaning – is not necessary. The facade may be glazed or glazed and sealed at a later stage. Prior to this treatment the facade has to be gently sanded and thoroughly cleaned.

General recommendations:

- /// We recommend a yearly inspection of the facade for damages
- /// Salamander outdoor profiles do not grey. Less intensive maintenance of profiles has no impact on the durability of the material.
- /// Since soiling can occur especially in areas exposed to direct spray-water and in the gable area, these surface areas should be sealed by employing RFS
- /// FVG and RFS were especially adapted to the properties of Salamander outdoor profiles. Therefore only these surface treatments may be employed for Salamander outdoor profiles.



Vertriebspartner | Representative:

GERCONA e.K.
Jahnstrasse 7 | 94065 Waldkirchen | Deutschland
Telefon +49 8581 989501 | Fax +49 8581 989502
office@gercona.com | www.gercona.com



SALAMANDER[®]
DECKING, FENCE & FACADE
MADE OF
Resysta[®]